

· TYPE _____ · DATE _____ · PROJECT _____

EXIT + EMERGENCY
Both in one unit

WET-LOCATION
Sealed for moisture

ALL LED
Efficient, long-life

SELF-TEST
Diagnostics on battery models

Tide

TID

GENERAL DESCRIPTION

A wet-location all-LED exit and emergency combo — sealed EXIT plus emergency egress for damp and wet spaces.

CONSTRUCTION & OPERATION

Long lasting, efficient, ultra bright white LED lamp heads.

3.6W (3 LEDs x 1.2 watt) per head.

Adjustable LED lamp heads provide optimal center-to-center spacing.

Long-life, energy efficient Red or Green LED EXIT sign illumination.



SPECIFICATIONS

Input Power	120/277 VAC; 24 VDC remote
Operating Temp	-20 °C – 50 °C
Housing	5VA flame retardant, UV stabilized
Warranty	Five year warranty
Listed to UL 924, NFPA 101; WET	

SELF-DIAGNOSTIC

UL 924 LISTED

ORDERING INFORMATION

Series	Faces	Letter	Housing
TID	1 – Single Face	R – Red	W – White
	2 – Double Face	G – Green	B – Black
			G – Gray (with white faceplate)

Ordering Example: TID-1-R-W

Options: CW Cold Weather · RC Remote Capacity · SDT Self Diagnostics · TP Tamper Proof Screws · CUSTOM Custom Wording

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”