

· TYPE _____ · DATE _____ · PROJECT _____

WET-LOCATION
Sealed against moisture

COMPACT
Small footprint

POLYCARBONATE
Durable, impact-resistant

DAMP RATED
Wet/damp location listed

Torrent

TOR

GENERAL DESCRIPTION

A compact wet-location polycarbonate exit sign — sealed against moisture for showers, garages, kitchens, and the building's damp edges.

CONSTRUCTION & OPERATION

Ultra bright, energy efficient, long life Red or Green LED.

Polycarbonate mounting canopy included for top or end mount.

Universal knockout pattern on back plate for wall mount.

Injection-molded, engineering grade, 5VA flame retardant, thermoplastic in White, Black or Gray finish.



SPECIFICATIONS

Input Power	Dual 120/277 voltage
Operation	BB · NB · REC · REP
Operating Temp	-20 °C to 50 °C
Warranty	Five year warranty
Listed to UL 924, NFPA 101; cETLus (Intertek); DAMP; WET	

DAMP RATED

SELF-DIAGNOSTIC

ORDERING INFORMATION

Series	Operation	Faces	Letter	Housing
TOR	BB – Battery Backup	1 – Single Face	R – Red	W – White
	NB – No Battery (AC)	2 – Double Face	G – Green	B – Black
	REC – Remote / Central			G – Gray
	REP – Remote DC / POE			

Ordering Example: TOR-REC-2-R-W-TP

Options: SDT Self-Diagnostics · 2C-120 Dual Circuit with 120V input · 2C-277 Dual Circuit with 277V input · 48 48V DC input · 60 60V DC input · TP Tamper-Proof · Custom Custom Wording

1 — Available only with BB Models 2 — Available only with NB units

LISTED TO



UL 924 / NFPA 101

“Engineered for the spaces it protects.”