

TYPE _____ · DATE _____ · PROJECT _____

CB COMPATIBLE
Factory ELC for central battery

ULTRA-THIN
Uniform backlit panel design

SELECTABLE CCT
3500K, 4000K, or 5000K

MULTI-MOUNT
Grid, surface, or cable mount

Willow

WIL

GENERAL DESCRIPTION

Ultra-thin LED backlit panel in aluminum frame with uniform illumination. 2x2 and 2x4 recessed or surface mount. Selectable lumen output and CCT.

Factory-installed ELC available for Sage central battery emergency compliance.

CONSTRUCTION & OPERATION

Aluminum frame with steel backplate.

PMMA lenses for uniform illumination.


Recessed grid, surface, or cable mount.

Selectable lumen output and CCT.

Universal 120-277VAC with 0-10V dimming.

Factory ELC for Sage central battery emergency operation.

cULus wet listed, IP65, L70 > 144,000 hours, DLC listed.



SPECIFICATIONS	
Sizes	2x2 / 2x4 / 1x4
Lumen Output	Selectable (3L to 11L)
CCT	3500K / 4000K / 5000K
Input	120-277 VAC
Lamp Life	L70 > 144,000 hours
Listings	cULus / DLC / IP65 / Wet
CB COMPATIBLE	
SAGE LIVE™ READY	

ORDERING INFORMATION

Series	Watts	Volts	CODE	OPTION / DESCRIPTION
PHL	40-50W	120-277VAC	2X2	2x2 Panel
			2X4	2x4 Panel
			ELCXX	Emergency Lighting Control

Ordering Example: PNL-2X4-40W-120-ELCXX



“Engineered for the spaces it protects.”