

· TYPE _____ · DATE _____ · PROJECT _____

OPEN FACE
Bold, high-visibility

ACCESSIBLE EXIT
Code-accessible egress

DIE-CAST
Slim, durable housing

DAMP RATED
Wet/damp location listed

XRAY

XRA

GENERAL DESCRIPTION

An open-face accessible-exit LED sign with a die-cast face and housing (max 5/8" single-face thickness) and uniform lighting — bold, accessible egress marking.

CONSTRUCTION & OPERATION

Ultra Slim die-cast aluminum LED emergency exit lighting system; the wall mount profile is 1/2" above the surface.

The die-cast outer housing contains a closely fitted acrylic lens. An LED array is recessed into the housing. The assembly is extremely rugged and can withstand severe impact and vibration without damage.

For even further protection, clear polycarbonate security covers are available.



SPECIFICATIONS

Input Power	Universal 120/277 VAC
Operation	BB · NB · REC · REM
Brightness	6 ft-Lambert (21 cd/m²)
Uniformity	Better than 4:1
LED Life	In excess of 20 years
Operating Temp	0 °C to 50 °C
Listed to UL 924, NFPA 101; cETLus (Intertek); BABA; BAA; DAMP	

DAMP RATED

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Faces	Graphics	Backgrd	Trim	Mount
XRA	BB – Battery Backup	1 – Single	R – Red	W – White	W – White	LE – Left End
	NB – No Battery (AC)		G – Green	B – Black	B – Black	RE – Right End
	REC – Remote / Central				BZ – Bronze	TW – Universal
	REM – Remote (Master)				BA – Brushed Aluminum	TV – Top Vertical
						WV – Wall Vertical

Ordering Example: XRA-NB-1-R-W-W-TW-DP-"X-RAY IN USE"

Options: DG Self-Diagnostic (BB Operation) · DP Damp Location · PEN Pendant MT 12" · REC Recess Kit · WG Wire Guard · DAC Dual AC Circuit · DW Directional Window Width 8 1/2"

LISTED TO



ASSEMBLED IN USA



"Engineered for the spaces it protects."