

· TYPE _____ · DATE _____ · PROJECT _____

55 FT SPACING
Fewer fixtures per corridor

RECESSED 4"
Clean ceiling, low profile

EFFICIENT
Maximum coverage per watt

SAGE LIVE™
Monitored on the central battery

Zenith

ZEN

GENERAL DESCRIPTION

A recessed 4-inch LED downlight spaced up to 55 ft in 9-ft ceilings — a highly efficient way to light long corridors for egress. Part of the Sage central battery system, monitored through Sage Live.


CONSTRUCTION & OPERATION

Operates with Sage central battery including low voltage normal lighting operation. (See Sage central battery data sheet)

Dual function operation for Night or Security lighting as well as emergency lighting.

Over 50,000 hour lamp life in normal use.

Self-Test Diagnostics is standard.



SPECIFICATIONS

Operation	BB · AC · RE
LED Life	50,000 hours
Operating Temp	BB 0–50 · AC/RE -40–50 °C
Warranty	10 year warranty

Listed to UL 924, NFPA 101; cETLus (Intertek); BABA; BAA

SELF-DIAGNOSTIC

UL 924 LISTED

ORDERING INFORMATION

Series	Operation	Power	Trim
ZEN	BB – Battery Backup	7 – 7 Watts (BB/RE)	W – Satin White
	AC – AC Supply, 120/277V	10 – 10 Watts (BB/RE)	K – Black
	RE – Remote with Central Battery	4 – 4 Watts (AC)	A – Aluminum
		7 – 7 Watts (AC)	B – Dark Bronze
			X – Custom

Ordering Example: ZEN-BB-10-W-DP

Options: DAC Dual AC Input (AC Models Only) · DP Damp Location

LISTED TO



ASSEMBLED IN USA



“Engineered for the spaces it protects.”